

Installation Instructions

Guimard Circular Chandelier

Important Safety Instructions

- Turn off all power to the Junction Box before making any electrical adjustments.
- Always disconnect the power before installing/replacing bulbs, during cleaning or maintenance.
- To avoid the risk of fire, do not exceed the recommended wattage.
- Consult a qualified, licensed electrician before installation.

To Assemble

1. Install the mounting disc to the J-box using the supplied machine screw hardware (2X).
2. Feed the electrical wires through the all thread. Then, attach the all-thread to the main body and slide the drop rod over it, flush with the main body.
3. There should be 1/2" of all thread above the tubing cover. If not, loosen the set screw and adjust. Secure the all thread by tightening the lock washer and nut.
4. Slide the canopy onto the all thread until flush with the tubing cover. Tighten the provided lock washer and nut to make a secure connection.
5. Connect the wires from the chandelier to those from the J-Box using the Wago wire connectors.
6. Push the ceiling plate over the mounting disc, flush with the ceiling and tighten with the provided lock washer (2X) and nut (2X). Cover with the finial (2X).
7. Attach the shades by sliding them onto the body arms. Alternate the brass (156X) and glass bars (156X) with a spacer inbetween (324X). Align the textured sides of the glass so they all face the same direction. At the end of each row secure with a thumb screw (12X).
8. Screw in the bulbs (12X) *DO NOT OVER TIGHTEN THE BULBS*
9. Turn on the power and check that good connections have been made.

Care Instructions

- Wipe with a soft cloth. Do not use chemical cleaner.

